

naujiena!



Oro užuolaidos ACA-A

Tipas	Oro srautas, m³/h	Galia, kW	Maitinimo tampa, V	Ilgis, cm	Svoris, kg	Kaina, Lt (be PVM)
ACA-A-060E	700	4	400	60	11,5	1905,00
ACA-A-090E	1050	6	400	90	16,5	2208,00
ACA-A-120E	1400	8	400	120	20,5	2441,00
ACA-A-180E	2100	12	400	180	29,5	3129,00
ACA-A-060F	700	4	230	60	11,5	1816,00
ACA-A-090F	1050	6	230	90	16,5	2105,00
ACA-A-120F	1400	8	230	120	20,5	2322,00
ACA-A-060S	700	-	230	60	11,0	1399,00
ACA-A-090S	1050	-	230	90	16,0	1629,00
ACA-A-120S	1400	-	230	120	20,0	1816,00
ACA-A-180S	2100	-	230	180	28,5	2449,00

A - ekonomin klas . **ACA-A-E** - elektrinis šildymas, trifazis; **ACA-A-F** - elektrinis šildymas, vienfazis; **ACA-A-S** - be šildytuvo. Nurodytas galingumas, kai oro temperat ra - +18°C. Pilkos spalvos. Valdymas - nuotoliniu infraraudon j spinduli pulteliu (yra komplekte).

naujiena!



Oro užuolaidos ACA-B

Tipas	Oro srautas, m³/h	Galia, kW	Maitinimo tampa, V	Ilgis, cm	Svoris, kg	Kaina, Lt (be PVM)
ACA-B-100E	1350	6	400	100	18,6	2755,00
ACA-B-150E	2000	9	400	150	22,7	3521,00
ACA-B-200E	2700	12	400	200	26,9	3799,00
ACA-B-100F	1300	9	400	100	19,7	3046,00
ACA-B-150F	1900	14	400	150	24,5	3895,00
ACA-B-200F	2550	18	400	200	29,3	4214,00
ACA-B-100S	1500	-	230	100	17,6	2196,00
ACA-B-150S	2200	-	230	150	20,9	2785,00
ACA-B-200S	2950	-	230	200	24,5	2992,00
ACA-B-100V	1100	8,9/7,3	230	100	22,7	2775,00
ACA-B-150V	1650	14,6/12	230	150	28,4	3511,00
ACA-B-200V	2200	20,1/16,7	230	200	34,4	3873,00

B - ekonomin klas . **ACA-B-E** - 1 pakopos elektrinis šildymas; **ACA-B-F** - 2 pakop elektrinis šildymas; **ACA-B-S** - be šildytuvo; **ACA-B-V** - vandeninis šildytuvai. Nurodytas galingumas, kai oro temperat ra - +18°C, vandens - 90/70°C/80/60°C. RAL 9010. Valdymas - laidiniu nuotoliniu pulteliu (yra komplekte), be vandeninio valdymo.



ORO UŽUOLAIDOS



Oro užuolaidos ACA-I

Tipas	Oro srautas, m³/h	Galia, kW	Maitinimo tampa, V	Ilgis, cm	Svoris, kg	Kaina, Lt (be PVM)
ACA-I-055E	3250	6	400	55	29,5	2648,00
ACA-I-150E	6350	12	400	150	79,0	4945,00
ACA-I-200E	10000	18	400	200	106,0	6693,00
ACA-I-055S	3500	-	400	55	25,0	1978,00
ACA-I-150S	6600	-	400	150	67,0	3686,00
ACA-I-200S	10200	-	400	200	90,0	4976,00
ACA-I-055V	2650	11,4/9	400	055	37,0	2514,00
ACA-I-150V	5250	25,9/21,3	400	150	99,0	4619,00
ACA-I-200V	8100	38,9/32	400	200	133,0	6449,00

I - pramonin klas . **ACA-I-E** - elektrinis šildymas; **ACA-I-V** - vandeninis šildytuvas, vienfaz ; **ACA-I-S** - be šildytuvo. RAL 9010.
Nurodytas galingumas, kai oro temperat ra - +18°C, vandens - 90/70°C/80/60°C.

Priedai: valdymo pultelis ACA-IC (užsakomas atskirai).

